



BM3400/S0

fanless

Industrial Automation - Products & Configurations

BM3400/S0 D0 BASIC SYSTEM					POWER [W]
Basic Configuration		Intel® Celeron® dual core G3900E 2,40 GHz • 4GB RAM • fanless • without predisposition to extractable drives • 24V DC isolated power supply • without UPS • UBIQUITY BASIC Win32/64 runtime • 12 month warranty			56
BM3400/S0 D1 BASIC SYSTEM					POWER [W]
Basic Configuration		Intel® Celeron® dual core G3900E 2,40 GHz • 4GB RAM • fanless • with predisposition to 1 extractable drive • 24V DC isolated power supply • without UPS • UBIQUITY BASIC Win32/64 runtime • 12 month warranty			56
BM3400/S0 D2 BASIC SYSTEM					POWER [W]
Basic Configuration		Intel® Celeron® dual core G3900E 2,40 GHz • 4GB RAM • fanless • with predisposition to 2 extractable drives • 24V DC isolated power supply • without UPS • UBIQUITY BASIC Win32/64 runtime • 12 month warranty			56
REMOTE ASSISTANCE	D0	D1	D2		↓
	•	•	•	ASEM UBIQUITY BASIC Win32/64 runtime	
PROCESSORS	•	•	•	Intel® Celeron® G3900E • 2,40 GHz, 2MB L2 cache • 2 cores, 2 threads • Soldered on-board	
	•	•	•	Intel® Core™ i3-6100E • 2,70 GHz • 3MB smart cache • 2 cores, 4 threads • Soldered on-board	+ 0
	•	•	•	Intel® Core™ i5-6440EQ • 2,70 GHz (3.40 GHz Turbo) • 6MB smart cache • 4 cores, 4 threads • Soldered on-board	+ 0
	•	•	•	Intel® Core™ i7-6820EQ • 2,80 GHz (3,50 GHz Turbo) • 8MB smart cache • 4 cores, 8 threads • Soldered on-board	+ 13
RAM MEMORY	•	•	•	4 GB • 1 module SODIMM DDR4-2133	
	•	•	•	8 GB • 2 x 4 GB modules SODIMM DDR4-2133	+ 1
	•	•	•	16 GB • 2 x 8 GB modules SODIMM DDR4-2133	+ 2
	•	•	•	32 GB • 2 x 16 GB modules SODIMM DDR4-2133	+ 3
INTERNAL PSU	•	•	•	Without UPS (uninterruptible power supply)	
	•	•	•	With UPS (uninterruptible power supply) • integrated in power supply section • batteries kit not included > note 1	+ 1
OPTIONS					POWER [W]
TPM	D0	D1	D2		↓
	•	•	•	TPM - Trusted Platform Module	0
CFAST	•	•	•	Cfast SATA	1
	•	•	•	SSD on mSATA connector onboard, SATA	2
HDD/SSD 2,5"	•	•	•	1 x HDD/SSD 2,5" SATA III internal installation kit (HDD/SSD not included)	-
	•	•	•	1 x HDD/SSD 2,5" SATA III extractable drawer (HDD/SSD not included)	-
	•	•	•	2 x HDD/SSD 2,5" SATA III extractable drawer (HDD/SSD not included)	-
	•	•	•	SSD 2,5" SATA	5
	•	•	•	HDD 2,5" SATA	6
COMMUNICATION PORTS	•	•	•	1 x RS232/422/485 (DB15M) • 1 x USB 2.0 > note 2	1
	•	•	•	1 x RS232/422/485 (DB15M) isolated • 1 x USB 2.0 > note 2	1
	•	•	•	2 x RS232 (DB9M) > note 2	2
	•	•	•	2 x USB 2.0 > note 2	0
FIELDBUS	•	•	•	1 x NETcore X card with "60pin-H" connector > note 2	3
	•	•	•	1 x additional video output RVL - Remote Video Link • Remotation up to 100m of DVI-D and USB 2.0 signals • without cables > note 3	3
REMOTE VIDEO LINK	•	•	•	2 x additional video output RVL - Remote Video Link • Remotation up to 100m of DVI-D and USB 2.0 signals • without cables > note 3	3
	•	•	•		
UPS BATTERY KIT	•	•	•	Batteries kit for detached systems mounting (wall mount) • 30cm cable included	15
	•	•	•	Batteries kit for detached mounting (wall mount) • 100cm cable included	15
WARRANTY EXTENSION	•	•	•	Warranty extension to 18 month	
	•	•	•	Warranty extension to 24 months	
	•	•	•	Warranty extension to 36 months	
	•	•	•		

NOTES	
The power consumption of the configuration takes into consideration the maximum absorbed power of every component and does not include the consumption of the devices connected to the USB ports.	
1: UPS module is supported by Microsoft Win32/64 operating systems.	
2: Communication boards cannot be installed together.	
3: RVL option is in addition to the DVI-D video output on the motherboard, allows the installation of max 1 extractable drawer and have to be connected to a MHR100 or MKR100 monitor or an external RVL module.	



BM3400/S0

fanless

TECHNICAL SPECIFICATIONS	
Case	Wall book mounting
Overall dimensions & weight	See details on the related section
Power supply	24VDC isolated • Input voltage: 18÷32V DC
UPS (optional)	12V DC UPS (Uninterruptible Power Supply) battery backup system Batteries module (optional): Pb, 12V/13A max, 2500mAh • Charge time 3h@25°C • Discharge time 15'@5A and 25°C • Lifetime 10years@25°C
Motherboard	"All-In-One" type • ASEM 1371
Watch dog	Time programmable
Intel platform	Processor Intel® Celeron® dual core 35W • Intel® Core® 6 th generation 35/45W Chipset Intel® HM170 PCH (Platform Controller Hub)
Operating System	O.S. certified by ASEM: Microsoft Windows 10 IoT Enterprise 2016 64bit • Microsoft Windows 8.1 Industry Pro 32/64bit • Microsoft Windows 7 Pro/Ultimate 32/64bit • Microsoft Windows Embedded Standard 7E/7P 32/64 bit • Linux O.S. not supported by Intel platform: Other operating systems, such as VxWorks, QNX, etc., have not been certified by ASEM but they are reasonably supported by the Intel platform after verification of compatibility
Software	Remote assistance: ASEM UBIQUITY BASIC Win32/64 runtime license with ASEM sticker
Video controller	Intel® HD Graphics 510 integrated into Intel® Celeron™ microprocessor • 950MHz Intel® HD Graphics 530 integrated into Intel® Core™ microprocessor • 950MHz / 1GHz
Video RAM (shared)	Dynamic Video Memory Technology • Memory quantity is automatically selected by operating system
System memory	DDR4-2133 type • 2 SODIMM modules • min 4GB • max 32GB
Mass storage interfaces	2 x SATA III, 6Gb/s • 1 x mSATA SATA III, 6Gb/s
RAID controller	Integrated into chip Intel® HM170 PCH • Raid 0, 1
TPM	2x10 (2,54) Pin-strip connector for optional TPM module
Front signalling (LED)	Power ON • UPS • HDD activity • Over temperature / Battery fault • Watchdog / Reset factory default
Front buttons (with open door)	Power ON • System Reset • Watchdog Reset • Factory Default Reset
On Top I/F	4 x Ethernet 10/100/1000 Mbps (RJ45), 3 x Intel® I210, 1 x Intel I219LM • 2 x USB 3.0 (Type A) • 2 x USB 2.0 (Type A) • 1 x RS232 (DB9M) • 1 x DVI-D Single Link (max resolution: 1920x1080 FullHD) optional: 1 or 2 x RVL OUT (RJ45), remotation (TX) up to 100 m of video DVI-D and USB 2.0 signals
On Front I/F (with open front door)	1 x slot CFast (bootable) • 1 x system battery slot (CR2032) • 1 x USB 3.0
Environmental specifications	Operating temperature: 0°C÷+50°C, 0°C÷+45°C with 24x7 HDD or with Core i7 processor, +5°C÷+45°C with standard HDD • Storage temperature: -10° ÷ +60°C • Humidity: 80% (non-condensing)
Approvals	CE (EN 55022, EN 61000-3-2/3, EN 55024, EN 60950-1) • cULus LISTED (UL61010) pending
Standard warranty	12 months • Warranty management by ASEM headquarters

OVERALL DIMENSIONS (mm)

